

SINGLE PALLET CNC HYDRAULIC PUMP PACKAGE

With Pressure Detection:

Part# 3183-MPA-1STN-P-PKG-CP

Without Pressure Detection:

Part# 3183-MPA-1STN-PKG-CP

PAWS WORKHOLDING
EFFICIENCY COMES STANDARD

The PAWS Workholding single valve pump package seamlessly integrates with any single pallet CNC. The pump easily connects to the inputs and outputs of your CNC control panel to allow M-Code activation and pressure sensing.

Air-Driven Double Acting Hydraulic Pump with 40:1 pressure ratio mounted on a 10 Litre reservoir with strainer, return filter and sight gage. Also includes an integral filter / regulator 1/2" NPT ports with 0-150 PSI air gage. Maximum 4,000 PSI pump pressure rating.

Package With Pressure Detection Includes:

- GX40 Double Acting Hydraulic Pump
- Single Station Manifold Block
- Qty one(1) 4-way, 3-position Directional Valves w 12mm Wire Leads
- Qty one(1) Pressure Monitoring Switch & Connection cable
- 24 Volt Power Supply
- I/O Board interface cable w four(4) Input/Output leads plus ground wire
- Dual Contact Circuit Breaker, 24V 15A Control Relay, Socket
- Protective Aluminum Casing



PLUG-AND-PLAY PUMP TECHNOLOGY



M-CODE ACTIVATION + PRESSURE DETECTION

